

# web

- [web](#)



## 1. 创建数据库

```
mysql -uroot -p123456
create database bookstack character set utf8mb4 collate utf8mb4_unicode_ci;
create user 'bookstack'@'localhost' identified by '123456';
grant all on bookstack.* to 'bookstack'@'localhost';
flush privileges;
exit;
```

## 2. 创建 .env 文件

```
cp .env.example .env
sed -i \
-e 's#^APP_URL=https://example.com#APP_URL=https://linuxnote.asia#' \
-e 's#^DB_HOST=localhost#DB_HOST=127.0.0.1#' \
-e 's#^DB_DATABASE=database_database#DB_DATABASE=bookstack#' \
-e 's#^DB_USERNAME=database_username#DB_USERNAME=bookstack#' \
-e 's#^DB_PASSWORD=database_user_password#DB_PASSWORD=123456' \
.env
cat >>.env<<'EOB'
APP_TIMEZONE=Asia/Shanghai
APP_VIEWS_BOOKSHELVES=list
APP_VIEWS_BOOKSHELF=list
APP_VIEWS_BOOKS=list
EOB

cat .env | grep -E
'APP_URL|DB_HOST|DB_DATABASE|DB_USERNAME|DB_PASSWORD|APP_VIEWS_BOOKSHELVES|APP_VIEWS_BOOKSHELF
|APP_VIEWS_BOOKS'
php artisan config:clear
```

## 3. 安装 composer 依赖

vendor

```
composer install --no-dev
```

## 4. app\_key

```
php artisan key:generate
```

```
cat .env | grep APP_KEY
```

## 5.

```
php artisan migrate --force
```

```
mysql -u bookstack -p123456 bookstack -e "show tables;"
```

## 6. nginx

```
chown -R nginx:nginx /web/BookStack-26.05.3
```

## 7.

```
chmod -R 755 /web/BookStack-26.05.3
```

## 8.

```
chmod -R 775 /web/BookStack-26.05.3/storage
```

```
chmod -R 775 /web/BookStack-26.05.3/bootstrap/cache
```

```
chmod -R 775 /web/BookStack-26.05.3/public/uploads
```

## 9. .env

```
chmod 600 /web/BookStack-26.05.3/.env
```

## 10. 部署

```
cd /web/BookStack-26.05.3
php artisan bookstack:create-admin --initial
# admin@example.com
# ioio9800-
```